

roll cage 2nd door bar question

Posted by nkgosselin - 31 May 2009 03:54

How many inches above the bar that comes welded from autopower do folks weld in the additional bar that comes with the cage?

Or, if you don't have autopower, how far apart are your door bars?

=====

Re:roll cage 2nd door bar question

Posted by Gary_44 - 31 May 2009 05:26

I don't remember seeing anything in the CCR about minimum separation.

I put mine below the inside door handle, low enough with padding to still use the handle. It's perfect level to rest my elbow on when seated, and ok for sitting on when getting in and out.

=====

Re:roll cage 2nd door bar question

Posted by joepaluch - 31 May 2009 09:54

There are no limits in the NASA CCR's. So it is up to you and whoever the cage builder/welder may be.

=====

Re:roll cage 2nd door bar question

Posted by Hanksville Hot Rods - 01 Jun 2009 12:24

I like to place my 944 door bars 6" apart (measured from the bottom of the top bar to the top of the bottom bar), with two spreaders between them. My upper door bar is approx. 13" from the top of the bar to the rocker at the point where it meets the forward hoop. There's no science to these numbers, but for most drivers the overall height seems to allow good ingress/egress (especially with "Extended-Style" door bars) while enabling retention of the factory door intrusion beam.